

RUPI CABLE- AND WIRESTOCKINGS. SIMPLY BRILLIANT AND INDISPENSABLE"

CUPI-COLOSNE", 6MbH

YOUR SPECIALIST AROUND CABLE AND

Cable and rope joining stockings

>> RP- 400



These stockings are designed for joining cables or ropes with the same diameter and without a lot of twist. This way it is, for example, possible to change crane ropes in one run or to include two cable lengths at once. In case of increased torsion of the cables etc. we

recommend using single stockings together with respective whirl shackles to compensate for the twist. This mesh of galvanized steel braids is woven with two strands, open on both ends and has no eyelets.





(2-layered / standard)



(3-layered / enhanced)

RP-400:

Available in standard lengths 1500 mm, 2000 mm and 3000 mm. Other lengths upon request! Also available in the following design:

- >> STAINLESS STEEL (STAINLESS STEEL BRAIDING)
- >> STAINLESS STEEL REINFORCED (three-layer design for higher tensile strength)
- >> STRAINED BOWDEN CABLE
- >> PLASTIC COATED STRANDS



rupi-Cologne, GmbH

Industriestr. 30-32 "Einfahrt Siemensstraße"

67269 Grünstadt Germany

Phone + Fax

+49(0)2234-95395-0 +49(0)2234-95395-22 E-mail + Web

info@rupi-cologne.de www.rupi-cologne.de



"RUPI CABLE- AND WIRESTOCKINGS,
SIMPLY BRILLIANT AND INDISPENSABLE"

CUPI-COLOSICE" EMBH

YOUR SPECIALIST AROUND CABLE AND WIRE

Cable and rope joining stockings

>> RP- 400

| For cables and ropes with ø from - to | Permissible tension load in kN / tons approx. | Thimble size for bolt ø approx. mm | Part number Please indicate required length/s (e.g. RP-410-1500) for stocking length 1500 |
|---------------------------------------|---|--|---|
| 06 - 08 mm | 3,60 / 0,37 | both sides open | RP - 406 - + length |
| 08 - 10 mm | 3,60 / 0,37 | both sides open | RP - 408 - + length |
| 10 - 15 mm | 5,12 / 0 ,52 | both sides open | RP - 410 - + length |
| 15 - 20 mm | 6,93 / 0,71 | both sides open | RP - 415 - + length |
| 20 - 30 mm | 8,67 / 0,88 | both sides open | RP - 420 - + length |
| 30 - 40 mm | 10,40 / 1,06 | both sides open | RP - 430 - + length |
| 40 - 50 mm | 21,36 / 2,18 | both sides open | RP - 440 - + length |
| 50 - 60 mm | 21,36 / 2,18 | both sides open | RP - 450 - + length |
| 60 - 80 mm | 28,48 / 2,90 | both sides open | RP - 460 - + length |
| 80 - 100 mm | 45,60 / 4,65 | both sides open | RP - 480 - + length |
| 100 - 120 mm | 50,67 / 5,17 | both sides open | RP - 4100 - + length |



Greater loads and higher tensile forces and special designs on request. Produceable immediately.

4.

Industriestr. 30-32 "Einfahrt Siemensstraße" 67269 Grünstadt Germany

rupi-Cologne, GmbH

Phone + Fax

E-mail + Web

info@rupi-cologne.de www.rupi-cologne.de

+49(0)2234-95395-0

+49(0)2234-95395-22